

AUX GROUP

Established in 1986, AUX Group is an enterprise which covers 5 industries. It ranked China's top 500 enterprises for consecutive years, 40000+ employees keep AUX fast development for recent years.

39 ^{Years}	\$12.4 ^{Billion}	5	\$ 9.6 ^{Billion}	500	40000+
History	Revenue in 2024	Business Industries	Assets	China's Top	Employees

R&D Strength

AUX Solar team is always adhered to the philosophy "quality is the footstone, innovation is the soul". We are market-oriented, focus on the analysis of product technology trends and based on the real demands of customers. In order to provide customers the best products and more values. We keep improving the core competitiveness of products, comprehensively to achieve product leadership in solar industry.



6 R&D centers



50+
Top experts in the industry



21261 Patents



100 million
Average annual investment



3 CNAS labs



5474 R&D
engineers

Ningbo AUX Solar Import & Export Co., Ltd.

No.17Fenglin Road, Cicheng Town,
Jiangbei District, Ningbo City, zhejiang Province, China



✉ info@auxsol.com
🌐 www.auxsol.com
☎ +86 0574-8765 2201



THREE PHASE
ON-GRID INVERTER

50-80kW-G2

THREE PHASE ON-GRID INVERTER



ASN-(50-80)TL-G2

KEY FEATURES



High Efficiency

- » Single MPPT supports a maximum current of 48A, single string supports a maximum current of 20A, compatible with 210 large modules
- » Supports oversizing 1.5x DC/AC
- » 180V low start-up voltage enables early startup and more energy generation



Smart

- » Ultra-wide grid voltage design with automatic voltage regulation technology ensures uninterrupted operation even under unstable grid conditions



Safe & Reliable

- » IP66 protection rating, adaptable to harsh operating environments
- » Intelligent AFCI reduces fire risk
- » Pure film capacitors with a 25-year design lifespan.



Economical & Cost-Saving

- » No power derating at 45°C, more reliable with more yield

	ASN-50TL-G2	ASN-60TL-G2	ASN-70TL-G2	ASN-75TL-G2	ASN-80TL-G2
Input DC					
Max.input power	75kW	90kW	105kW	112.5kW	120kW
Max.input voltage	1100V				
Rated voltage	630V				
Start-up voltage	180V				
MPPT voltage range	150-1000V				
Max.input current	40A*4	48A*4			
Max.short circuit current	50A*4	60A*4			
MPPT number	4	4			
Max. input strings number	8	12			
Output AC					
Rated output power	50kW	60kW	70kW	75kW	80kW
Max.apparent output power	55kVA	66kVA	77kVA	82.5kVA	88kVA
Max.output power	55kW	66kW	77kW	82.5kW	88kW
Rated grid voltage	220V/380V,230V/400V,3/N/PE				
Grid voltage range	162-300V(Phase voltage),280-520V(Line voltage)				
Rated grid frequency	50Hz/60Hz				
Rated grid output current	72.2A	86.6A	101A	108.3A	115.5A
Max.output current	79.4A	95.3A	111A	119.1A	127A
Power factor	>0.99 (0.8 leading ... 0.8 lagging)				
THDi	<3%				
Efficiency					
Max. efficiency	98.60%				
EU efficiency	98.30%				
MPPT efficiency	>99.8%				
Protection					
Integrated DC switch	Yes				
DC rever-polarity protection	Yes				
Anti-islanding protection	Yes				
Short circuit protection	Yes				
Output over current protection	Yes				
DC Surge protection	Type II				
AC Surge protection	Type II				
Insulation impedance detection	Yes				
Ground fault monitoring	Yes				
Residual leakage current detection	Yes				
Temperature protection	Yes				
AC Over voltage protection	Yes				
DC Over current protection	Yes				
Strings monitoring	Optional				
24-hour load monitoring	Optional				
Integrated AFCI (DC arc-fault circuit protection)	Optional				
Integrated PID recovery	Optional				
Anti-backflow	Optional				
General Data					
Dimensions (W*H*D)	735*530*285mm				
Weight	60kg				
Self consumption(night)	<1W				
Operating temperature range	-30...+60℃				
Cooling concept	Fan-cooling				
Max. operation altitude	4000m (Derating above 3000m)				
Relative humidity	0-100%				
Ingress protection	IP66				
Topology structure	Transformerless				
Grid connection standard	NB/T32004,EN 50549-1,IEC 63027,PORTARIA N°515,CGC/GF 035-2013				
Safety/EMC standard	IEC/EN 62109-1/2,EN IEC 61000-6-2/4,EN IEC 61000-3-11,EN 61000-3-12				
Type of DC terminal	MC4 connector				
Type of AC terminal	OT terminal				
Display&Communication					
Display	LED+Bluetooth+APP(Optional:LCD)				
Communication Interface	RS485,Optional:WIFI,4G,LAN				

Note: The specification and key features described in this datasheet may deviate slightly and are not guaranteed. AUXSOL reserves the right to make any adjustment to the information described herein at any time without notice. Please always obtain the latest version of the datasheet, any commercial contracts that may be signed will be based on the most recent version at the moment of signing the contract.